

DocuPrint P225 d/db M225 dw / M225 z A4 Monochrome Printers

Delivering performance and productivity with clever connectivity



Powerful, efficient performers

The Fuji Xerox DocuPrint P225 d / M225 dw / M225 z are the perfect solution for personal use or small workgroups requiring high quality, efficient monochrome printing together with flexible connectivity capabilities.

Performance and reliability

- **Speed and quality.** With a print resolution of up to 2400 x 600 dpi and printing speeds of 26 ppm across the 225 Series, they deliver quality print results fast.
- All-in-one functionality. Multifunction models allow you to print, copy, scan and fax* in an efficient, low cost device giving you maximum productivity.
- Clever features for reliable operation.
 Fuji Xerox is renowned for reliable printing.
 The DocuPrint P225 d / M225 dw / M225 z are no exception with simple engineering and clever new ideas designed for trouble-free printing.

*Only available on DocuPrint M225 z

Affordable, efficient printing

- Low cost hardware is only half of the story. Thanks to the separate toner and drum cartridge, you will only ever have to replace one component at a time. This results in maximum use of each component, longer operating times and cost savings.
- Save toner save cost. Toner save mode extends the life of the toner cartridge by varying the density of toner that is printed on a page.
- Use less paper and toner. The built in N-UP print feature gives users the ability to save on paper and toner by printing multiple pages on a single sheet of paper. This also reduces the overall cost of printing.



Easily connect and print via your iOS or Android devices

AirPrint and Google Cloud Print Ready



AirPrint™ and Google Cloud Print™ enables you to print directly from your mobile device without the need to download mobile apps or to install print drivers.





Wi-Fi Direct

The DocuPrint M225 dw / M225 z are Wi-Fi Direct $^{\text{\tiny M}}$ certified, allowing devices to connect and print easily without requiring a wireless access point.



Print Utility



Whether it's an iOS or Android device, the Fuji Xerox Print Utility puts mobile printing at your fingertips. Print stored photo albums, web pages or shoot and print on the go from your iOS or Android device.

Fuji Xerox Print Utility can be easily downloaded from the App Store for iOS and Play Store for Android devices.









Print from anywhere Google Cloud Print allows you to connect your printers to the web, so you can make your home and work printers available to you from the applications you use every day, from wherever you are.

DocuPrint M225 z 4-in-1 Wireless Multifunction Laser Printer



Smart features increase productivity

Duplex printing as standard

Enjoy increased productivity and cost savings with Duplex printing as standard across the entire printer lineup.

Clever ID Card Copying*

The easy-to-use ID card copy feature allows you to copy both sides of the card onto the same side of the paper. Simply place an ID card both face up & down on the copier surface, pressing the start button each time. There is no need to change the position of the cards when copying the other side, as the feature automatically adjusts this for you.



*Available on multifunction models



DocuPrint P225 d Network Laser Printer



DocuPrint M225 dw 3-in-1 Wireless Multifunction Laser Printer



DocuPrint M225 z 4-in-1 Wireless Multifunction Laser Printer

DocuPrint P225 d/db / M225 dw / M225 z Specifications

Product Name	DocuPrint P225 db DocuPrint P225 c		DocuPrint M225 z	
Function	A4 monochrome printer	A4 monoc	hrome MFP	
Print Function		1 la ta 26 a a a 1	11- t- 261	
Print Speed (A4) Print Resolution	Up to 26 ppm ¹	Up to 26 ppm ¹	Up to 26 ppm ¹	
First-page-out Time (A4 SEF) (from ready	Up to HQ1200 technology (2400 x 600 dpi quality)			
mode)		8.5 second or less		
Warm-up Time		9 seconds or less (from sleep mode)		
Memory	32MB	64 MB	64MB	
PDL Processor	DCL6 Host Pased	266 MHZ	DCL6 Hast Resed	
Colour Touchscreen	PCL6, Host-Based	PCL6, Host-Based	PCL6, Host-Based	
Connectivity	10 Base-T/100Base	p-TX	-	
	Hi-Speed USB2.0 Ethernet	Wireless, 10 Base-T/100Base	-TX Ethernet, USB2.0 Hi-Speed	
Nietowali wasta and familia and dia with	USB2.0 Hi-Speed	T	DNC LLAAND d LDD/LDD. Ct D	
Network protocol for models with network function	Port/Port 9100 IPP FTP Server S	to 1P), W1N3/NetB1U3 name resolution, DN3 resolver, I NIMPv1/v2c/v3 HTTP Server TETP Client and Server S	MDNS, LLMINK responder, LPK/LPD, Custom Kaw MTP Client ICMP Web Services (Print)	
The Work Turnetion	IPv6 : NDP, RA, DNS Resolver, mDNS, LLMN	ub (1P), WINS/NetBIOS name resolution, DNS resolver, NMPv1/v2c/v3, HTTP Server, TFTP Client and Server, S Responder, LPR/LPD, Custom Raw Port/ Port 9100, LP Client and Server, SMTP Client, ICMPv6, Web Services	P, FTP Server, SNMPv1/v2c/v3, HTTP Server, TFTP	
MIN DO	-	Client and Server, SMTP Client, ICMPv6, Web Services	(Print)	
Mobile Print Supported Operating System	- AirPrint, Google Cloud Print, FX Print Utility for iOS and Android Windows Vista®, 7, 8, Windows® 8.1, Server 2003 / 2003 x64 Edition / 2008 / 2008 R2 / 2012 / 2012 R28, Mac OS X v, 10.7.5, 10.8.x, 10.9.x³			
Duplex Printing	windows Visita", 7, 8, windows" 8.1, Server 2003 / 2003 x04 Edition / 2008 / 2008 / 2012 / 2012 / 2012 K2", Mac US X V, 10.7.5, 10.8.X, 10.9.X" Automatic			
Input Paper Size (Paper Tray)	A4 SEF, Letter SEF, A5 SEF/LEF, A6 SEF, Executive SEF, Folio (8.5° x 13") SEF, Legal SEF, 16K(China only), 210x270mm (Taiwan only)			
Media Input Capacity (Paper Tray)	250 sheets 80gsm			
Media Input Capacity (manual feed slot)	1 sheet			
Input Paper Size (Manual Feed slot)		Width 76.2~216 mm, Length 127~355.6mm		
Media Output Capacity	100 sheets 80gsm (Face down), 1 sheet (Face up with rear cover open)			
Media Types (Main Tray, or Duplex)	Plain pager, This			
Media Types (Manual Feed slot)	Plain paper, Thin Paper, Thick Paper, Recycled paper, label, envelope, bond paper			
Input Paper Weight (Paper Tray) Input Paper Weight (Manual Feed slot)	60 to 105 gsm 60 to 163 gsm			
Automatic Document Feeder	=		ets (64-90 gsm)	
Single pass Duplex Automatic Document		, Op to 33 silet	50 (0) 50 gsiii/	
Feeder				
Monthly Maximum Duty Cycle		10K pages	TD) W.	
Print Features	Ioner Save Mode, N-up(2,4,9,16, or 25) ⁴ , P	Poster ⁵ (4,9,16,25), Header/Footer ⁵ (time & date and/or	user ID), Watermarks ⁵ , manual duplex printing ⁵ ,	
Dimensions (WxDxH)	356 x 360 x 186 mm	manual booklet printing ⁵ 409 x 398.5 x 316.5 mm	409 x 398.5 x 316.5 mm	
Weight (without supplies)	5.9 kg	10.7 kg	11.1 kg	
Operating Environment Temperature	3.3 mg	Storage: 0° C to 40° C, Operating: 10° C to 32.5°		
Humidity	Op	perating Environment: 20% to 80%RH (without conde		
Acoustics: Sound Pressure level		Printing: 50 dB(A)		
Electrical Power		220–240 VAC, 50/60 Hz		
Power consumption ¹⁰	Ready/Standby: 58W ENERGY STAR® qualified	Ready/Standby: 60W ENERGY STAR® gualified	Ready/Standby: 60W ENERGY STAR® qualified	
TEC value	1.0 k Wh/w	1.2 k Wh/w	1.2 k Wh/w	
Wireless Specification	1.0 K WII/W	1.2 K WII/W	1.2 K WII/W	
Wireless LAN	_	IEEE 802.11b/g/n (Infrastructure/Ad-ha	oc Mode) IEEE 802.11g/n (Wi-Fi Direct™)	
Wireless Network Security	_		(TKIP/AES), WPA2-PSK(AES)	
Network security (Wireless)	=	SMTP-AU1	TH. SNMP v3	
Wireless Certification	_	Wi-Fi Certification Mark License (WPA/WPA2-F	Personal), Wi-Fi Protected Setup (WPS) Identifier Wi-Fi CERTIFIED Wi-Fi Direct	
C		Mark Licensee, AUSS Logo,	Wi-Fi CERTIFIED Wi-Fi Direct	
Copy Function Copy Speed (A4)	_	Linto	26 cpm ¹	
Copy Resolution			0 x 600 dpi	
First-copy-out Time	_		ss; ADF : 11 seconds or less	
Reduction / Enlargement	_		1% increments	
Multi-Copy	-		to 99	
Copy Feature	_	ID Card Copy, N in 1 copying	(N=2,4), sort(up to 99 pages)	
Automatic 2-sided copy	_	-	_	
Scan Function			···· CIC	
Type Automatic 2-sided scan		Colo	ur CIS	
Scanning Resolution	-	Ontical (Scanner Glass) up to 600 v 1	200 dni (mono) 600x2400 dni (colour)	
Jeanning Nesolution	_	Enhanced: up to	Optical :(Scanner Glass) up to 600 x 1200 dpi (mono), 600x2400 dpi (colour) Enhanced: up to 19,200 x 19,200 dpi	
			0 x 600 dpi (mono/colour)	
Scan Depth	_	Colour 24 bit. Mo	nno 8bit Grav Scale	
Document Size	_	Platen: max 21	5.9mm x 300mm 9mm x Length 147.3 – 355.6mm	
C B		ADF: max Width 147.3 – 215.9	9mm x Length 147.3 – 355.6mm	
Scan Destinations	_	Scan to PC and application (Email,	Image, File) by ControlCenter utility	
Supported Driver	_	Windows : I WAIN, WIA for Windows Visto	1°/Windows® 7/Windows® 8 /Windows® 8 .1 OS 10.7.5/10.8.x/10.9.x	
Fax Function		ivide i vvaliv, ica loi v	03.07.3/10.0///10.3/	
Compatibility	_	_	ITU-T Super G3	
Communication System	-	-	PSTN	
Modem Speed	-	-	33.6 Kbps	
Memory Transmission	=	-	Up to 500 pages ⁷	
Out-of-paper reception	_	_	Up to 500 pages ⁷	
Fax Resolution	_	_	Superfine 8dot/mm x 15.4line/mm	
Speed Dials Broadcasting	_		Up to 200 locations	
Broadcasting Fax Features			Up to 258 locations PC Fax Send and Receive⁵	
Handset			- rc rax seria aria receive	
Warranty	One Year Drop-in Warranty		ıy on-site warranty	
		, one year next de	,	
•				
Consumables				
	1,200 ⁸ pages to	oner (225 Series) / 2,6008 pages toner (265 Series) and	d 12,000 ⁹ pages drum	
Shipped consumables (approx.) Standard Capacity Toner cartridge (approx.) ⁸	1,200 ⁸ pages to	CT202329 (1,200 pages)	d 12,000° pages drum	
Consumables Shipped consumables (approx.) Standard Capacity Toner cartridge (approx.) High Capacity Toner cartridge (approx.) Drum Cartridge (approx.)	1,200 ⁸ pages to		d 12,000° pages drum	

Pinit/copy speed may decrease due to factors such as paper type, paper size, and printing conditions. ² Measured diagonally. ³ Mac drivers are available by web download. ⁶ N-up for Mac (2,4,6,9, or 16). ⁸ Windows Only. ⁶ Max 1200 x 1200 dpi scanning with WIS (Windows Image Acquisition) driver in Windows Vista, Windows 7 and Windows 8. ² ITU-T Test Chart, Standard resolution. ⁸ Declared yield in accordance with ISO/IEC 19752. Yield will vary based on image area coverage and print mode. ⁹ Drum yield may vary by the type of use. ⁹⁹ Measured when the machine is connected to the USB interface. This product has been tested and found to comply with the Class 1 Laser Equipment requirements defined by the international standard IEC60825-1:2007 and has no light exposure hazard. The product has no hazardous light emission as it features light protection compens and covers to shut in all light beam during operation and maintenance. Internal Laser radiation. Wave length: 770 - 800 nm. Output: 25 mW max. Laser Class: Class 3B















For more information or detailed product specification, please call or visit us at

Fuji Xerox (Hong Kong) Limited

8/F, Cityplaza 3, 14 Taikoo Wan Road, Quarry Bay, Hong Kong Tel: (852) 2513 2646 Fax: (852) 2513 2968

Website: www.fujixeroxprinters.com.hk

